

Boa™ Industrial Suction & Discharge Hose is manufactured and designed for medium - high pressure applications. The water suction hose is made from premium quality EPDM/SBR blend coupled with nylon cord and embedded helix steel wire. These materials combined provide outstanding performance, with increased abrasion resistance and tensile strength. This allows for a long service life and excellent weather resistance.

### ORDERS & CUSTOMER SERVICE

1 (888) 893-5GCP  
sales@gcpindustrial.com

#### OIL SUCTION HOSE - 100 Ft. Lengths

SIZE	GCP Part #	WP (PSI)	BP (PSI)	Length	Wt./Ft. [lbs.]	Total Wt [lbs.]
1"	09-OSH-150-1.00	150	450	100	1	67.07
2"	09-OSH-150-2.00	150	450	100	2.75	184.45
3"	09-OSH-150-3.00	150	450	100	4	268.29
4"	09-OSH-150-4.00	150	450	100	5	335.37
6"	09-OSH-150-6.00	150	450	100	7.75	519.82

**Tube:** Black Oil Resistant Rubber

**Reinforcement:** Nylon cord with helix steel wire embedded

**Cover:** Black Oil Resistant Rubber

**Temperature Range:** -25°F to 200°F

**Branding:** As required



*Capitalize on **YOUR** sales opportunity with this great **GCP** product!*

#### WATER SUCTION HOSE - 100 Ft. Lengths

SIZE	GCP Part #	WP (PSI)	BP (PSI)	Length	Wt./Ft. [lbs.]	Total Wt [lbs.]
1"	09-WSH-150-1.00	150	450	100	0.67	67.07
1 1/2"	09-WSH-150-1.50	150	450	100	1.01	100.61
2"	09-WSH-150-2.00	150	450	100	1.84	184.45
3"	09-WSH-150-3.00	150	450	100	2.68	268.29
4"	09-WSH-150-4.00	150	450	100	3.35	335.37
6"	09-WSH-150-6.00	150	450	100	5.20	519.82

**Tube:** Black EPDM blend

**Reinforcement:** Nylon cord with helix steel wire embedded

**Cover:** Black EPDM blend

**Temperature Range:** -25°F to 175°F

**Branding:** As required

GCP Industrial Products

1 (888) 893-5GCP

© GCP Elastomeric Inc. 2010



170 Webster Road, Kitchener, ON N2C 2E6 \* P: 519-893-8207 \* F: 519-893-9356  
E: [sales@gcpindustrial.com](mailto:sales@gcpindustrial.com) \* W: [www.gcpindustrial.com](http://www.gcpindustrial.com)